

NovaJet™ PhotoGloss PE Paper 240 WR

For thermal and piezo inkjet printing of water-resistant prints for proofing and photographic applications

Product Description & Application

NovaJet PhotoGloss PE Paper 240 WR (PGP wr 240) is a PE coated paper, top-coated with glossy ink-receptive layer. It is suitable for proofing applications and Indoor applications such as high resolution posters for photographic prints, GIS imaging & remote sensing applications.

Features & Benefits

- Compatible with most water-based dye & pigment inks for printing on wide variety of inkjet printers.
- High whiteness for wide colour gamut and deep rich colours.
- High opacity for limited show-through.
- High image definition and line clarity for better resolution and sharper proofs.
- Water-resistant media for longer life of printed image.
- Good colour stability for long lasting prints when kept away from direct sunlight.
- Minimal optical brighteners for accurate proofing outputs.

Product Specifications

- Base : PE coated paper
- Thickness : 240 gsm (± 5 gsm)
- Surface Finish : White glossy
- Ink Compatibility : Water-based Dye & Pigment Inks
- Ink Limit : Up to 360% with Dye Inks, 280% & above with Pigment Inks
- Shelf-life : One year from the date of manufacture when stored in original packing at 20-25° C and 50% rH.
- Availability : 432 mm x 20 mtrs; 610 mm x 20 mtrs; 914 mm x 20 mtrs; 1057 mm x 20 mtrs; 1270 mm x 20 mtrs

Compatibility with Water-based Dye & Pigment Inks

Ink Type	PRINTER															
	Encad			HP					Roland	Epson				Canon		
	500, 600 & 700 Series	850 Series	1000i & 1200i Series	DesignJet Z2100 / Z3100	DesignJet 430 / 750	DesignJet 1xx / 5xx / 8xx	DesignJet 1xxx / 4xxx	DesignJet 2xxx / 3xxx / 5xxx	Hi-fi Jet Series & Super Hi-fi Jet	Stylus 7000 / 9000 / 10000	Stylus 7500 / 9500	Stylus 4000 / 7600 / 9600 / 10600	Stylus 10000 CF	Stylus 4800 / 7800 / 9800	Image Pro Graph 6200 / 8200	Image Pro Graph 6400 / 8400
Dye	★	★	★	★	★	★	★	★	★	★	—	★	—	★	★	—
Pigment	×	×	×	—	×	×	×	×	★	—	★	—	★	—	—	★

★ Superior Compatibility

× Non Compatibility

⊙ Under Testing

— Not Applicable

◆ Tested with Original Inks.

◆ While printing on dye-based ink compatible media using HP DesignJet Printer Models 1xx / 5xx / 8xx & 430 / 750, 1xxx / 4xxx, use "PhotoGloss" media profile for printing.

⊠ The Epson Stylus 4000 / 7600 / 9600 / 10600 series are tested with UltraChrome Inks and Epson Stylus 4800 / 7800 / 9800 with K3 inks respectively.

contd...

Durability In Indoor Conditions

- The durability of the printed image is dependent on the fading characteristics of the inks used. Please consult the ink manufacturer for technical advice.
- If the printed graphics are likely to be exposed to corrosive liquids, smoke, fumes or a highly polluted atmosphere or if there is a likelihood of scratching or friction, it is strongly recommended that the prints are laminated with a UV stabilised vinyl lamination film with a solvent-based adhesive.
- NovaJet PhotoGloss PE Paper 240 WR, when printed and protected as indicated above (with a laminate), can have an image life expectancy of up to 3 months.

Usage Instructions

- It is recommended to condition the media in the normal printing environment for 24 hours before printing.
- While printing, care must be taken to modify the print file to suit the ink limit of the media. For best results, please ensure proper colour calibration. For further assistance, please consult our Applications Experts or contact our HelpDesk.
- The media should be printed on within the specified ink limit. Exceeding the ink limit can lead to longer drying time, bleeding, lower resolution and poor adhesion of the lamination film.
- Printed media should be thoroughly dried before rolling-up for transport to avoid ink smearing.
- A fresh pair of cotton gloves should be used while handling the bare media to avoid sweat, grease and oil transfer on to the media that could interfere with the print quality.
- When not in use, the media should be stored in its original packing, in a vertical position.

Corporate Office

TechNova Imaging Systems (P) Limited

Laxmi Mills Estate, Off Dr. E. Moses Road
Mahalaxmi, Mumbai 400 011, India
Phone : +91 (0)22 2741 2463
Fax : +91 (0)22 2741 0261
eMail : corp@technovaworld.com
Web : www.technovaworld.com

HelpDesk

Toll-free : 1 800 22 7474 (*Only available in India*)
Phone : +91 (0)22 2741 2464 (Extn. 600)
Fax : +91 (0)22 2740 1366
eMail : help@technovaworld.com

UK office

Phone : +44 (0)20 8427 6662
Fax : +44 (0)20 8427 1162
eMail : europe@technovaworld.co.uk

Dubai office

Phone : +971 50 4590655
Fax : +971 4 8810166

Sri Lanka office

Phone : +94 1153 79926
Fax : +94 1153 31098

Branch Offices

Ahmedabad

Phone : +91 (0)79 2640 5048
Fax : +91 (0)79 2640 5492

Bangalore

Phone : +91 (0)80 2320 1103
Fax : +91 (0)80 2320 6898

Chennai (Madras)

Phone : +91 (0)44 2499 0028
Fax : +91 (0)44 2499 3512

Delhi

Phone : +91 (0)11 2331 9636
Fax : +91 (0)11 4160 5163

Hyderabad

Phone : +91 (0)40 2776 6241
Fax : +91 (0)40 2776 6251

Kochi (Cochin)

Phone : +91 (0)484 235 0768
Fax : +91 (0)484 237 4270

Kolkata (Calcutta)

Phone : +91 (0)33 2359 4256
Fax : +91 (0)33 2359 4254

Mumbai (Bombay)

Phone : +91 (0)22 2498 3390
Fax : +91 (0)22 2495 0322

